



ACJT04H-1000SW 4A TRIAC

Rev.A.1.0

The ACJT04H-1000SW triac is suitable for general purpose AC switching. It can be used as an ON/OFF function in applications such as heating regulation, induction motor starting circuits, for phase control operation in light dimmers, motor speed controllers. The ACJT04H-1000SW embeds a TVS structure to absorb the inductive turn-off energy such as those described in the IEC 61000-4-5 standards. Package TO-251 is RoHS compliant.

Symbol	Value	Unit
$I_{T(RMS)}$	4	A
V_{DRM}/V_{RRM}	1000	V

 $\nabla_a \nabla_p V$

Parameter	Symbol	Value	Unit
Storage junction temperature range	T_{stg}	-40-150	
Operating junction temperature range	T_j	-40-125	
Repetitive peak off-state voltage ($T_j=25^\circ C$)	V_{DRM}	1000	V
Repetitive peak reverse voltage ($T_j=25^\circ C$)	V_{RRM}	1000	V
RMS on-state current ($T_c = 98^\circ C$)	$I_{T(RMS)}$	4	A
Non repetitive surge peak on-state current (full cycle , $t_p=20ms$, $T_j=25^\circ C$)	I_{TSM}	40	A
Non repetitive surge peak on-state current (full cycle , $t_p=16.6ms$, $T_j=25^\circ C$)		44	
I^2t value for fusing ($t_p=10ms$, $T_j=25^\circ C$)	I^2t	8	A^2s
Critical rate of rise of on-state current ($I_G=2I_{GT}$, $f=100Hz$, $T_j=125^\circ C$)	dI/dt	50	$A/\mu s$
Peak gate current ($t_p=20\mu s$, $T_j=125^\circ C$)	I_{GM}	4	A
Average gate power dissipation ($T_j=125^\circ C$)	$P_{G(AV)}$	0.5	W
Peak gate power	P_{GM}	10	W

ACJT04H-1000SW

Peak pulse voltage (T _j =25 °C; non-repetitive, off-state; FIG.7)	V _{PP}	3.25	kV
---	-----------------	------	----

(T_j=25 °C unless otherwise specified)

Symbol	Test Condition	Quadrant	Value		Unit
I _{GT}	V _D =12V R _L =33	- -	MAX.	10	mA
V _{GT}		- -	MAX.	1	V
V _{GD}	V _D =V _{DRM} T _j =125 °C R _L =3.3K	- -	MIN.	0.2	V
I _L	I _G =1.2I _{GT}	-	MAX.	30	mA
				45	
I _H	I _T =100mA		MAX.	25	mA
dV/dt	V _D =670V Gate Open T _j =125 °C		MIN.	250	V/μs
(dI/dt)c	(dV/dt)c=10V/μs, T _j =125 °C		MIN.	3.5	A/ms
t _{on}	I _G =20mA I _A =200mA I _R =20mA T _j =25 °C	TYP.	2.5	25	μs
t _{off}					
V _{CL}	I _{CL} =0.1mA t _p =1ms		MIN.	1050	V

Symbol	Parameter		Value(MAX.)	Unit
V _{TM}	I _{TM} =5.6A t _p =380μs	T _j =25 °C	1.6	V
V _{TO}	Threshold voltage	T _j =125 °C	0.9	V
R _D	Dynamic resistance	T _j =125 °C	80	mΩ
I _{DRM}	V _D =V _{DRM} V _R =V _{RRM}	T _j =25 °C	8	μA
I _{RRM}		T _j =125 °C	0.4	mA

Symbol	Parameter	Value	Unit
R _{th(j-c)}	junction to case (AC)	4.5	/W
R _{th(j-a)}	junction to ambient (AC)	120	/W





FIG.1 Maximum power dissipation versus RMS on-state current




FIG.2: RMS on-state current versus case temperature





FIG.7 Test circuit for inductive and resistive loads to IEC-61000-4-5 standards




Refer to Instructions for installation of plastic-sealed in-line power devices released by JieJie

Order code	Voltage V_{DRM}/V_{RRM} (V)	IGT(mA)	Package	Base qty. (pcs)	Delivery mode
ACJT04H-1000SW	1000	10	TO-251	80	Tube

Document Revision History

Date	Revision	Changes
Apr.14, 2023	A.1.0	Last updated



Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.

 is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright ©2023 Jiangsu JieJie Microelectronics Co., Ltd. Printed All rights reserved.