


**DESCRIPTION:**

The ACJT105-6W triac is suitable for general purpose AC switching. It can be used as an ON/OFF function in applications such as heating regulation, induction motor starting circuits, for phase control operation in light dimmers, motor speed controllers. The ACJT105-6W embeds a TVS structure to absorb the inductive turn-off energy such as those described in the IEC 61000-4-5 standards. Package SOT-223-2L is RoHS compliant.

**MAIN FEATURES**

Symbol	Value	Unit
$I_{T(RMS)}$	1	A
V_{DRM}/V_{RRM}	600	V
$I_{GT} / /$	5/5/5	mA

ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Value	Unit
Storage junction temperature range	T_{stg}	-40-150	
Operating junction temperature range	T_j	-40-125	
Repetitive peak off-state voltage ($T_j=25^\circ C$)	V_{DRM}	600	V
Repetitive peak reverse voltage ($T_j=25^\circ C$)	V_{RRM}	600	V
RMS on-state current ($T_c = 90^\circ C$)	$I_{T(RMS)}$	1	A
Non repetitive surge peak on-state current (full cycle , $t_p=20ms$, $T_j=25^\circ C$)	I_{TSM}	15	A
Non repetitive surge peak on-state current (full cycle , $t_p=16.6ms$, $T_j=25^\circ C$)		16.5	
I^2t value for fusing ($t_p=10ms$, $T_j=25^\circ C$)	I^2t	1.25	A^2s
Critical rate of rise of on-state current ($I_G=2mA$, I_{GT} , $f=100Hz$, $T_j=125^\circ C$)	dI/dt	50	$A/\mu s$
Peak gate current ($t_p=20\mu s$, $T_j=125^\circ C$)	I_{GM}	2	A
Average gate power dissipation ($T_j=125^\circ C$)	$P_{G(AV)}$	0.1	W
Peak gate power	P_{GM}	5	W

ACJT105-6W

Peak pulse voltage (T _j =25 °C; non-repetitive, off-state; FIG.8)	V _{PP}	3.5	kV
---------------------------------------------------------------------------------	-----------------	-----	----

ELECTRICAL CHARACTERISTICS (T_j=25 °C unless otherwise specified)

Symbol	Test Condition	Quadrant	Value		Unit
I _{GT}	V _D =12V R _L =33	- -	MAX.	5	mA
V _{GT}		- -	MAX.	1	V
V _{GD}	V _D =V _{DRM} T _j =125 °C R _L =3.3K	- -	MIN.	0.2	V
I _L	I _G =1.2I _{GT}	-	MAX.	10	mA
				20	
I _H	I _T =100mA		MAX.	10	mA
dV/dt	V _D =400V Gate Open T _j =125 °C		MIN.	700	V/μs
(dI/dt)c	(dV/dt)c=10V/μs, T _j =125 °C		MIN.	0.5	A/ms
t _{on}	I _G =10mA I _A =200mA I _R =20mA T _j =25 °C	TYP.	2	20	μs
t _{off}					
V _{CL}	I _{CL} =0.1mA t _p =1ms		MIN.	700	V

STATIC CHARACTERISTICS

Symbol	Parameter		Value(MAX.)	Unit
V _{TM}	I _{TM} =1.1A t _p =380μs	T _j =25 °C	1.4	V
V _{TO}	Threshold voltage	T _j =125 °C	0.8	V
R _D	Dynamic resistance	TA6BDC	0.004 Tc -0.002 Tw 2j4 32a f 56.88 30 Td <021D>n	

FIG.1 Maximum power dissipation versus RMS on-state current




FIG.2: RMS on-state current versus case temperature




FIG.3: RMS on-state current versus ambient temperature (printed circuit board FR4,copper thickness:35μm)(full cycle)




FIG.4: Surge peak on-state current versus number of cycles




FIG.5: On-state characteristics




FIG.6: Non-repetitive surge peak on-state current for a sinusoidal pulse with width $t_p < 20\text{ms}$, and corresponding value of I^2t ($dI/dt < 50\text{A}/\mu\text{s}$)

FIG.7: Relative variations of gate trigger current, holding current and latching current versus junction temperature





FIG.8 Test circuit for inductive and resistive loads to IEC-61000-4-5 standards




ORDERING INFORMATION

Order code	Voltage V_{DRM}/V_{RRM} (V)	IGT(mA)	Package	Base qty. (pcs)	Delivery mode
ACJT105-6W	600	5	SOT-223-2L	4,000	Tape & Reel

Document Revision History


Date	Revision	Changes
Apr.13, 2023	A.1.0	Last updated

PACKAGE MECHANICAL DATA



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	1.50	1.60	1.80	0.059	0.063	0.071
A1	0.01	0.06	0.10	0.001	0.002	0.004
B	2.90	3.00	3.10	0.114	0.118	0.122
B1	0.60	0.70	0.80	0.024	0.028	0.031
C	0.22	0.254	0.32	0.009	0.010	0.013
D	6.30	6.50	6.70	0.248	0.256	0.264
E	3.30	3.50	3.70	0.130	0.138	0.146
F	4.40		4.80	0.173		0.189
F1	2.20		2.40	0.087		0.094
G	0.50		1.00	0.020		0.039
H	1.50	1.75	2.00	0.059	0.069	0.079
J	6.70	7.00	7.30	0.264	0.276	0.287
K	0.80		1.00	0.031		0.039

FOOTPRINT-SOT-223-2L (dimensions in mm)



Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.

 is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.
Copyright ©2023 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.